

Headache-Free connectivity for your IoT & M2M applications.



OptConnect_neo2

Features

- Plug-n-play High-speed connectivity
- Lightweight 2.8 oz
- Compact size 2.7" x 2.2" x 0.7"
- Rugged Aircraft grade Aluminum,
 Temp resistance -40c +85


Additional Features


- Cost-effective replacement for landline dialup circuits or analog cell-phones – Primary connectivity for PLCs, RTUs, POS, ATM solutions
- Dual-carrier redundancy
- Backup/redundant network connections for LANs
- High speed data transfer rate
- Full duplex transceiver ethernet port
- LED network and signal indicators
- Remotely manageable and upgradeable

Advantages

- Primary network connectivity for micro markets, kiosks, signs, POS, ATMs, etc.
- Dual-carrier redundancy
- Delivers speed and wide coverage (Cellular Technology 4G LTE)
- Flexible and practical
- Flexible mounting options
- 5v power
- Enables remote device connectivity
- Always on
- Low power consumption 4G 10-12.5 watts peak
- Built-in Firewall 2.2
- DHCP server for local automatic IP assignment can assign static IPs
 NAT with VPN Passthru
 Domain name addressable
- High-Speed Data Connections







| Wireless WAN | |
|------------------------|--|
| LTE CAT 4 | FDD B2[1900], B4[1700], B5[850], B12[700], B13[700], B14[700], B66[1700], B71[600] |
| | B2[1900], B4[1700], B5[850] |
| SIM Slots | 2 internal 3FF Micro-SIM Slot |
| Antenna Connectors | 2 x 50 ΩSMA (Center pin: female) |
| Ethernet | |
| Ports | 2 |
| Connector | RJ-45 |
| Standard | IEEE 802.3 |
| Physical Layer | 10/100 Base-T |
| Data Rate | 10/100 MBit/s |
| Mode | Full or Half duplex |
| Interface | Auto MDI/MDIX |
| Management | |
| Fully Managed Service | OptConnect Portal |
| Processor and Memory | Atheros AR9331, 64MB RAM, 16MB FLASH |
| Protocol Support | HTTP, HTTPS, FTP, SSL |
| Power | |
| Input | 5 VDC (power supply with barrel connector included) |
| Consumption | Typical: 3.5 W; Max: 12.5 W |
| General | |
| LEDs | Power On, LAN Connection, signal quality, cell activity |
| Relative Humidity | 5% to 95% (non-condensing) |
| Approvals | |
| GSM/CDMA | Verizon ODI, PTCRB, AT&T |
| Carrier Certifications | Certified by Verizon PTCRB, AT&T, and most major carriers |



AVS Companies avscompanies.com

(847) 439-9400

info@avscompanies.com

